



Components	Specs
Dome	4.5 mm High Impact Clear Acrylic.
MAXLIGHT 550 Flat - RoundFlashing	2 mm Aluminium
Top, Extension & Bottom tubes	0.5mm Aluminium with 98% reflectivity.
Transition Box	ABS designed to suit grid or gyprock ceiling with surrounding décor trim
Square Diffuser	Acrylic Lens assembled in square Aluminium Frame

NOTES
 1. STRUCTURAL ELEMENTS SHOWN FOR REFERENCE ONLY
 2. ALL DIMENSIONS IN METRIC MM

SOLAR BRIGHT AUSTRALIA PTY LTD
 11 Progress Circuit. Prestons. NSW. 2170 Australia.

ALL DIM IN MM DO NOT SCALE 3RD ANGLE PROJECTION AS1100 THIS PRINT	Sunday, 2 July 2023 3:33:24 PM
THIS IS THE CONTROL DRAWING FOR THE CAD FILE: DRAWINGNAME-REVISION.EXTENSION	SHEET SIZE SHEET NUMBER SHEET SCALE
GENERAL TOLERANCES (UNLESS OTHERWISE STATED): X = ±1.000 X.XX = ±0.250 X.XXX = ±0.025 (X) = REF. DIM.	A0 1 / 1 NA
DRAWING NAME	REVISION



MAXLIGHT 550 UNIVERSAL
 FOR SUSPENDED CEILING GRID

B