



Components	Specs
Dome	3.6mm High Impact Clear Acrylic.
Top, Extension & Bottom tubes	0.5mm Aluminium with 98% reflectivity.
Diffuser Kit	Acrylic Lens in Decor Trim
Maxlight 250 Corrugated Roof Flashing	Polypropylene

NOTES  
STRUCTURAL ELEMENTS SHOWN FOR REFERENCE ONLY  
ALL DIMENSIONS IN METRIC MM

**SOLAR BRIGHT AUSTRALIA PTY LTD**  
11 Progress Circuit. Prestons. NSW. 2170 Australia.

ALL DIM IN MM	DO NOT SCALE	3RD ANGLE PROJECTION	AS1100	THIS PRINT	Tuesday, 27 June 2023 4:57:11 PM
THIS IS THE CONTROL DRAWING FOR THE CAD FILE: DRAWINGNAME-REVISION.EXTENSION				SHEET SIZE	SHEET NUMBER
GENERAL TOLERANCES (UNLESS OTHERWISE STATED):				A0	1 / 1
X. = ±1.000 X.X = ±0.250				NA	REVISION
X.XX = ±0.025 (X) = REF. DIM.					

DRAWING NAME  
**MAXLIGHT 250 CORRUGATED FOR GYPROCK - HARD CEILING**



B