

MaxBreeze Specifications (400 series)

Model	MB400S - Standard
Overview	Works During Day & Night Solar Powered AC Power Optional
Opening Size	370mm
Panel Size	40W / 20V
Colour	Black
Panel Shape	Square
Thermostat	On 25°C (+/-3°C) Off 18°C (+/-3°C)
Motor	IP65 Brushless DC
Panel Direction	Adjustable to face North
Flashing	Leak Proof to Suit Most Australian Roofs
Approx. Capacity	2,200m ³ /h (Capacity at Optimum Solar Conditions)
Nighttime Operation	Via Supplied 2-Pin AC Plug
Noise Level	Quiet (<44dB)
Applications	Residential & Commercial
Warranty	Motor 5 / Solar Panel 10 Years

Model	MB400Z - Zephyr
Overview	Works During Day & Night Solar Powered AC Power Optional
Opening Size	370mm
Panel Size	40W / 20V
Colour	Black
Panel Shape	Square
Thermostat	On 25°C (+/-3°C) Off 18°C (+/-3°C)
Motor	IP65 Brushless DC
Panel Direction	Adjustable to Face North
Flashing	Leak Proof to Suit Most Australian Roofs
Approx. Capacity	2,200m ³ /h (Capacity at Optimum Solar Conditions)
Night time Operation	Via Integrated Battery
Noise Level	Quiet (<44dB)
Applications	Residential & Commercial
Warranty	Battery 3 / Motor 5 / Solar Panel 10 Years

