

MaxLight tubular Skylights Specifications

ML250 & ML400

Size	Product Code
250mm	K-ML250
400mm	K-ML400

Roof Dome	250mm & 400mm hail resistant, crystal clear surface for maximum performance, UV stabilised acrylic, non-yellowing.						
Roof Flashing	One-piece seamless leak proof moulded flashings, functioning as base support for top tube and dome, UV stabilised to suit most roof types. Colour match optional.						
Adjustable Tube (Angle Adaptors)	Durable anodized solid aluminium, 300mm long top adaptor and 300mm long bottom adaptor, specular reflectance 98%; tubing is anodised for high protection from prolonged sun exposure and is not laminated. It will not yellow, fade or delaminate.						
Extension Tubes (ordered separately)	Durable solid aluminium, 400mm or 600mm long, specular reflectance 98%, tubing is anodised for high protection from prolonged sun exposure and is not laminated. It will not yellow, fade or delaminate.						
Ceiling Ring	White ABS injection moulded.						
Décor Trim	Injection moulded, durable with modern white finish.						
Diffuser Assembly	Multi-layer lens, with white frame and optional finish of Auroramax®, Aurora, Prismax, Warm.						
Accessories	Fasteners, seals, and adhesive tape supplied with product by the manufacturer. Dimmers sold separately.						
Warranty	Industry leading 20 Year warranty.						
Performance	<ul style="list-style-type: none"> • Tested by NFRC approved laboratory. • Meets Australian standard AS4825-2007. • Meets Building Code Australia requirements. <table border="1" style="margin: 10px auto;"> <thead> <tr> <th>Product</th> <th>SHGC</th> <th>U-Factor</th> </tr> </thead> <tbody> <tr> <td>K-ML250 & K-ML400</td> <td>0.27</td> <td>2.46</td> </tr> </tbody> </table>	Product	SHGC	U-Factor	K-ML250 & K-ML400	0.27	2.46
Product	SHGC	U-Factor					
K-ML250 & K-ML400	0.27	2.46					
Country of origin	Australian owned, designed and made.						

