

## MaxLight tubular Skylight Specifications

### ML550

<b>Roof Dome</b>	510mm diameter, hail resistant clear acrylic dome, UV stabilised, non-yellowing.						
<b>Roof Flashing</b>	Non-corrosive flashings, leak proof designed to suit tile, Colourbond, and other metal roof profiles. Supports dome and top tube elbow as per manufacturers design. Can be colour matched.						
<b>Adjustable Tube (Angle Adaptors)</b>	Durable anodized solid aluminium, 300mm long top adaptor and 300mm long bottom adaptor, specular reflectance 98%; tubing is anodised for high protection from prolonged sun exposure and is not laminated. It will not yellow, fade or delaminate.						
<b>Extension Tubes (ordered separately)</b>	Durable solid aluminium, 400mm or 600mm long, specular reflectance 98%, tubing is anodised for high protection from prolonged sun exposure and is not laminated. It will not yellow, fade or delaminate.						
<b>Ceiling Finish – Square transition Box</b>	White square transition box from round tube to square 605mm x 605mm ceiling diffuser to suit suspended grid or gyprock ceilings.						
<b>Diffuser Assembly</b>	Multi-layer, square with white frame and optional finish of Aurora, Prismax OR Warm.						
<b>Accessories</b>	Fasteners, seals, and adhesive tape supplied with product by the manufacturer. Dimmers sold separately.						
<b>Warranty</b>	Industry leading <b>20</b> Year warranty.						
<b>Performance</b>	<ul style="list-style-type: none"> <li>• Tested by NFRC approved laboratory.</li> <li>• Meets Australian standard AS4825-2007.</li> <li>• Meets Building Code Australia requirements.</li> </ul> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Performance</th> <th>SHGC</th> <th>U-Factor</th> </tr> </thead> <tbody> <tr> <td>ML550</td> <td>0.24</td> <td>1.66</td> </tr> </tbody> </table>	Performance	SHGC	U-Factor	ML550	0.24	1.66
Performance	SHGC	U-Factor					
ML550	0.24	1.66					
<b>Country of origin</b>	Australian owned, designed and made.						

